

INDUSTRIAL COMPONENT DATA

MKDSN 2,5/ 2 RD 1714636 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 2,5/ 2 RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 2,5/ 2 RD
Catalog number	1714636
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-8251FF1838
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, dimensioning voltage (III/2): 400 V, nominal section: 2.5 mm², Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, article family: MKDSN 2.5, pitch: 5 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, Conductor connection direction/printed circuit board: 0 °, color: red, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, packaging type: boxed packaging. The item can be aligned with different numbers of poles!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1714636

Packing unit 1

GTIN 4055626369198

Custom tariff number 85369010

Item properties

Brief article description PCB terminal block

Range of articles MKDSN 2,5

Pitch 5 mm

Number of positions 2

Connection method Screw connection with tension sleeve

Screw thread M3

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 1

Number of connections 2

Number of potentials 2

Electrical parameters

Rated current 24 A

Rated insulation voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Connection capacity

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG / kcmil 24 ... 14

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.2 mm² ... 0.75 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 0.75 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 1.5 mm²

Stripping length 6.5 mm

Torque 0.5 Nm ... 0.6 Nm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics Tin-plated

Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 2,5/ 2 RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.