INDUSTRIAL COMPONENT DATA

SAC-8P-M12MS/ 5,0-PUR/M12MS SH 1572773 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-M12MS/ 5,0-PUR/M12MS SH

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-M12MS/ 5,0-PUR/M12MS SH
Catalog number	1572773
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-28F717F8FB
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, shielded, M12 straight male connector, coding: A-coded, a M12 straight male connector, coding: A-coded, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1572773
Packing unit 1 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356416917
Weight per Piece (excluding packing) 295.300 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
General
Rated current at 40°C 2 A
Rated voltage 30 V AC
30 V DC
Number of positions 8
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation LiF9YC11Y
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 8x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation approx. 0.2 mm
Wire colors Brown, white, green, yellow, gray, pink, blue, red
Overall twist 8 wires around filler to the core
Shielding Tinned copper braided shield
Optical shield covering 85 %
External sheath...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-M12MS/ 5,0-PUR/M12MS SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.