INDUSTRIAL COMPONENT DATA

CC 2,5/17-GF-LR P20 THR 1836832 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: CC 2,5/17-GF-LR P20 THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	CC 2,5/17-GF-LR P20 THR
Catalog number	1836832
Category	Printed circuit board connector
Minimum order	52 Pcs
Document ID	EO-81FBABE019
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Base housing printed circuit board, nominal section: 2.5 mm², color: black, rated current: 12 A, sizing voltage (III/2): 320 V, surface contacts: Tin, contact type: Male, Number of potentials: 17, Number of rows: 1,Number of poles per row: 17, number of connections: 17, article family: DC 2.5/.. -GF-LR, pitch: 5 mm, mounting: THR welding, pin arrangement: Linear pin arrangement, pin length [P]: 2 mm, Stecksystem: CLASSIC COMBICON, Locking: Lace locking, packaging type: boxed packaging
PCB headers, nominal cross section: 2.5 mm2, color: black, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Pin, number of potentials: 17, number of rows: 1, number of positions: 17, number of connections: 17, product range: CC 2,5/..-GF-LR, pitch: 5 mm, mounting: THR soldering / wave soldering, pin layout: Linear pinning, solder pin [P]: 2 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2,5, Pin connector pattern alignment: Standard, locking: Lock-and-release locking system, mounting: Lock & release threaded flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type PCB headers
Product family CC 2,5/..-GF-LR
Product line COMBICON Connectors M
Type Component suitable for through hole reflow

Number of positions 17
Pitch 5 mm
Number of connections 17
Number of rows 1
Number of potentials 17
Mounting flange Lock & release threaded flange
Pin layout Linear pinning
Solder pins per potential 1
Data management status
Article revision 02
Electrical propertiesNominal current IN 12 A
Nominal voltage UN 320 V
Contact resistance 1.1 m?
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 400 V
Rated surge voltage (II/2) 4 kV
MountingMounting type THR soldering / wave soldering
Pin layout Linear pinning
Flange
Tightening torque 0.3 Nm
Processing notes
Process Reflow/wave soldering
Moisture Sensitive Level MSL 1
Classification temperature Tc 260 °C
Solder cycles in the reflow 3
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface contact area (top layer) Tin (3 - 5 µm Sn)
Metal surface contact area (middle layer) Nickel (1.3 - 3 µm Ni)
Metal surface soldering area (top layer) Tin (3 - 5 µm Sn)
Metal surface soldering area (middle layer) Nickel (1.3 - 3 µm Ni)
Material data - housing
Color (Housing) black (9005)
Insulating material LCP
Insulating material group IIIa
C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CC 2,5/17-GF-LR P20 THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.