INDUSTRIAL COMPONENT DATA

VAL-MS 400/3+0/VF-FM 2910476 PHOENIX CONTACT Type 2 surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 400/3+0/VF-FM



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-MS 400/3+0/VF-FM
Catalog number	2910476
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-83CC767919
Generated	2026-11-18

Product Overview

Type 2 surge protection device
3-channel surge protection device, for mounting on NS 35/7.5, with remote indication (FM) contact as switch, 400 V AC voltage

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2910476
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626459172
Weight per Piece (excluding packing) 393.500 g
Custom tariff number 85363010
Country of origin DE (Germany)
Dimensions
Height 98.7 mm
Width 71 mm
Depth 65.7 mm (incl. DIN rail 7.5 mm)
Horizontal pitch 4 Div.

Ambient conditions
Degree of protection IP20 (only when all terminal points are used)
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 5000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)
General
IEC test classification II
T2
EN type T2
Mode of protection L-PE
L-L
Mounting type DIN rail: 35 mm
Color jet black RAL 9005
Housing material PA 6.6
PBT
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type DIN rail module, two-section, divisible
Number of positions 4
Surge protection fault message Optical, remote indicator contact
Additional descriptions
Note Burst test up to 4 kV passed according to DIN EN 61000-4-4.
Insulates against repetitive pulses up to 1.5 kV.
Only usable in IT Systems between L-PE, if the exposed-conductive-parts (bodies) of the equipment of the low-voltage installation is connected to the earthing arrangement of the transformer substation (interconnected earthing arrangement of the HV-transformer substation with the bo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 400/3+0/VF-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.