INDUSTRIAL COMPONENT DATA

MCDN 1,5/ 2-G1-3,5 OG RNP26THR 1704815 PHOENIX CONTACT Base housing, rated current: 8 A, sizing voltage (III..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDN 1,5/ 2-G1-3,5 OG RNP26THR

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDN 1,5/ 2-G1-3,5 OG RNP26THR
Catalog number	1704815
Category	Printed circuit board connector
Minimum order	105 Pcs
Document ID	EO-2EB1C53850
Generated	2026-11-19

Product Overview

Base housing, rated current: 8 A, sizing voltage (III/2): 160 V, number of poles: 2, pitch: 3.5 mm, color: orange, contact surface: Tin, mounting: Solder THR
Printed circuit board base housing, nominal section: 1.5 mm², color: orange, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 2, number of poles: 2, number of connections: 4, family of articles: MCDN 1.5/.. -G1-RN-THR, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Socket protrusion, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Header, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 2, pitch: 3.5 mm, color: orange, contact surface: Tin, mounting: THR soldering
Your advantages
Designed for integration into the SMT soldering processIntuitive locking mechanism prevents accidental disconnectionConductor connection on several levels enables higher contact densityKey Commercial Data
Orderkey 1704815
Packing unit 1

GTIN 4046356739375
Custom tariff number 85366930
General
Range of articles MCDN 1,5/..-G1-RN-THR
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Color orange
Number of positions 2
Standards and Regulations
Connection in acc. with standard EN-VDE
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
eCl@ss
eCl@ss 4.0 272607xx
eCl@ss 4.1 27260701
eCl@ss 5.0 27260701
eCl@ss 5.1 27141190
eCl@ss 6.0 27260704
eCl@ss 7.0 27440402
eCl@ss 8.0 27440402
eCl@ss 9.0 27440402
ETIM
ETIM 3.0 EC001121
ETIM 4.0 EC002637
ETIM 5.0 EC002637
ETIM 6.0 EC002637
UNSPSC
UNSPSC 6.01 30211810
UNSPSC 7.0901 39121409
UNSPSC 11 39121409
UNSPSC 12.01 39121409
UNSPSC 13.2 39121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDN 1,5/ 2-G1-3,5 OG RNP26THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.