
INDUSTRIAL COMPONENT DATA

MCDN 1,5/ 3-G1-3,5 P26 THRR32 1037403 PHOENIX CONTACT Feed-through header MCDN 1,5/ 3-G1-3,5 P26 THRR32 1037..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCDN 1,5/ 3-G1-3,5 P26 THRR32



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCDN 1,5/ 3-G1-3,5 P26 THRR32
Catalog number	1037403
Category	Printed circuit board connector
Minimum order	110 Pcs
Document ID	EO-CF941823B3
Generated	2026-11-19

Product Overview

Feed-through header - MCDN 1,5/ 3-G1-3,5 P26 THRR32 - 1037403
Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 6, number of rows: 2, number of poles: 3, number of connections: 6, family of articles: MCDN 1.5/.. -G1-THR, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 32 mm wide strap
PCB headers, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 3, pitch: 3.5 mm, color: black, contact surface: Tin, mounting: THR soldering, pin layout: Linear pinning, solder pin [P]: 2.6 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1037403
Packing unit 1
GTIN 4055626569192
Custom tariff number 85366930
Drawings
General
Classifications

Dimensions
Environmental Product Compliance
Drawings
Diagram
Type: FMC 1,5/...-ST-3,5 with MCDN 1,5/...-G1-3,5 P26THR
Back to topDimensions
Length [l] 13.3 mm
Width 12 mm
Pitch 3.5 mm
Dimension a 7 mm
Width [w] 12 mm
Height [h] 15.2 mm
Height 16 mm
Length of the solder pin 2.6 mm
Pin dimensions 0.8 x 0.8 mm
Pin spacing 3.50 mm
Length 13.3 mm
Back to topGeneral
Range of articles MCDN 1,5/..-G1-THR
Color black
Number of positions 3
Back to topEnvironmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Back to topClassifications
eCl@ss
eCl@ss 4.0 27260700
eCl@ss 4.1 27260700
eCl@ss 5.0 27260700
eCl@ss 5.1 27260700
eCl@ss 6.0 27260700
eCl@ss 7.0 27440402
eCl@ss 8.0 27440402
eCl@ss 9.0 27440402
Back to topETIM
ETIM 5.0 EC002637
ETIM 6.0 EC002637
ETIM 7.0 EC002637
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCDN 1,5/ 3-G1-3,5 P26 THRR32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.