INDUSTRIAL COMPONENT DATA

MCV 1,5/ 2-G-3,5 GY7035 AU 1032357 PHOENIX CONTACT Feed-through header MCV 1,5/ 2-G-3,5 GY7035 AU 1032357

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 2-G-3,5 GY7035 AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 2-G-3,5 GY7035 AU
Catalog number	1032357
Category	Printed circuit board connector
Minimum order	250 Pcs
Document ID	EO-7D90C3073E
Generated	2026-11-19

Product Overview

Feed-through header - MCV 1,5/ 2-G-3,5 GY7035 AU - 1032357
Printed circuit board base housing, nominal section: 1.5 mm², color: light gray, nominal current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Gold, contact type: Male, Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, number of connections: 2, family of articles: MCV 1.5/.. -G, pitch: 3.5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, Stecksystem: MINI COMBICON, Locking:without, packaging type: boxed
PCB headers, nominal current: 8 A, rated voltage (III/2): 160 V, nominal cross section: 1.5 mm², number of positions: 2, pitch: 3.5 mm, color: light gray, contact surface: Gold, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.4 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1032357
Packing unit 1
GTIN 4055626536255
Custom tariff number 85366930
Drawings
Electrical parameters

Material data - housing
Dimensions for PCB design
Ambient conditions
Mechanical tests (A)
Climatic tests (D)
Vibration test
Classifications
Item properties
Material data - contact
Dimensions for the product
Packaging information
Air clearances and creepage distances
Durability tests (B)
Environmental and durability tests (E)
Environmental Product Compliance
Drawings
Diagram
Type: MC 1,5/...-ST-3,5 with MCV 1,5/...-G-3,5
Diagram
Type: MCVW 1,5/...-ST-3,5 with MCV 1,5/...-G-3,5
Diagram
Type: FK-MCP 1,5/...-ST-3,5 with MCV 1,5/...-G-3,5
Diagram
Type: FMC 1,5/...-ST-3,5 with MCV 1,5/...-G-3,5
Back to topItem properties
Brief article description Feed-through header
Plug-in system MINI COMBICON
Type of contact Male connector
Range of articles MCV 1,5/..-G
Pitch 3.5 mm
Number of positions 2
Mounting type Wave soldering
Pin layout Linear pinning
Number of levels 1
Number of connections 2
Number of potentials 2
Back to topElectrical parameters
Nominal current 8 A
Nom. voltage 160 V
Rated voltage 160 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 250 V
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Back to topMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface cont...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 2-G-3,5 GY7035 AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.