
INDUSTRIAL COMPONENT DATA

MCV 1,5/20-G-3,5-RN GY 1710693 PHOENIX CONTACT Housing base printed circuit board, number of poles: 20, pitc..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/20-G-3,5-RN GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/20-G-3,5-RN GY
Catalog number	1710693
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-FBFFFBE0ED
Generated	2026-11-19

Product Overview

Housing base printed circuit board, number of poles: 20, pitch: 3.5 mm, color: gray, surface contacts: Tin
Printed circuit board base housing, nominal section: 1.5 mm², color: gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 20, number of rows: 1, number of poles: 20, number of connections: 20, family of articles: MCV 1.5/.. -G-RN, pitch: 3.5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Socket protrusion, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Socket for printed circuits, nominal current: 8 A, rated operating voltage (III/2): 160 V, number of poles: 20, pitch: 3.5 mm, color: gray, surface of contact: Tin, assembly: Soldering wave
Commercial data
The code for the order One million seven hundred ten thousand six hundred ninety three
Pieces/pack. 50 PCS
Sales key AAAEDA -
The amount of minimum order 50 PCS
GTIN Four trillion fifty five billion six hundred twenty six million one hundred sixty nine thousand nine hundred ten
Weight per piece (package included) 5,280 g
Number customs tariff Eighty five million three hundred sixty six thousand nine hundred ninety

Environmental Product Compliance
China RoHS Period for proper use: unlimited = EFUP-and
Any hazardous substances above the threshold values
Rankings
eCl@ss
eCl@ss 5.1 Twenty seven million two hundred sixty thousand seven hundred
eCl@ss 6.0 Twenty seven million two hundred sixty thousand seven hundred
eCl@ss 7.0 Twenty seven million four hundred forty thousand four hundred two
eCl@ss 8.0 Twenty seven million four hundred forty thousand four hundred two
eCl@ss 9.0 Twenty seven million four hundred forty thousand four hundred two
ETIM
ETIM 5.0 EC002637
ETIM 6.0 EC002637
ETIM 7.0 EC002637
UNSPSC
UNSPSC 13.2 Thirty nine million one hundred twenty one thousand four hundred nine

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/20-G-3,5-RN GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.