
INDUSTRIAL COMPONENT DATA

MCV 1,5/ 3-G-3,81 P26 THRR32 L 1785786 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 3-G-3,81 P26 THRR32 L



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 3-G-3,81 P26 THRR32 L
Catalog number	1785786
Category	Printed circuit board connector
Minimum order	200 Pcs
Document ID	EO-66D7933592
Generated	2026-11-19

Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MCV 1.5/.. -G-THR, pitch: 3.81 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 32 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1785786
Packing unit 1
GTIN 4046356647328
Custom tariff number 85366930
Dimensions
Length [l] 7.25 mm
Width 12.82 mm
Pitch 3.81 mm
Dimension a 7.62 mm

Width [w] 12.82 mm
Height [h] 11.8 mm
Height 9.2 mm
Length of the solder pin 2.6 mm
Pin dimensions 0.8 x 0.8 mm
Length 7.25 mm
General
Range of articles MCV 1,5/..-G-THR
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Color black
Number of positions 3
Standards and Regulations
Connection in acc. with standard EN-VDE
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 3-G-3,81 P26 THRR32 L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.