INDUSTRIAL COMPONENT DATA

MCV 1,5/ 6-G-3,5 P26 THR 3CP 1707326 PHOENIX CONTACT Base housing, rated current: 8 A, number of poles: 6, p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 6-G-3,5 P26 THR 3CP

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 6-G-3,5 P26 THR 3CP
Catalog number	1707326
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-8AE6D67709
Generated	2026-11-19

Product Overview

Base housing, rated current: 8 A, number of poles: 6, pitch: 3.5 mm, color: black, contact surface: Tin, mounting: Solder THR

Printed circuit board base case, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: MCV 1.5/.. -G-THR, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Soket, nominal akim: 8 A, pin sayisi: 6, pin araligi: 3,5 mm, renk: siyah, kontak yüzeyi: Kalay, montaj: THR lehimleme

Your advantages

Designed for integration into the SMT soldering processVertical connection enables multi-row arrangement on the PCBMaximum flexibility when it comes to device design - one header for connectors with different connection technologiesKey Commercial Data

Orderkey 1707326

Packing unit 1

GTIN 4046356918749

Custom tariff number 85366930

General
Range of articles MCV 1,5/..-G-THR
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Color black
Number of positions 6
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
eCl@ss
eCl@ss 5.1 27260701
eCl@ss 6.0 27260704
eCl@ss 8.0 27440402
eCl@ss 9.0 27440402
ETIM
ETIM 5.0 EC002637
ETIM 6.0 EC002637
UNSPSC
UNSPSC 13.2 39121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 6-G-3,5 P26 THR 3CP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.