INDUSTRIAL COMPONENT DATA

MCVR 1,5/ 4-ST-3,81KMGYBD:1-4 1705910 PHOENIX CONTACT Plug-in part, rated current: 8 A, number of poles: 4, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCVR 1,5/ 4-ST-3,81KMGYBD:1-4



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCVR 1,5/ 4-ST-3,81KMGYBD:1-4
Catalog number	1705910
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-282A728384
Generated	2026-11-19

Product Overview

Plug-in part, rated current: 8 A, number of poles: 4, pitch: 3.81 mm, connection type: Screw connection with traction capsule, color: light gray, contact surface: Tin
Connector for printed circuit board, nominal section: 1.5 mm², color: luminous gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MCVR 1.5/.. -ST, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, connection direction conductor/printed circuit board: 90 °, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Plug component, nominal current: 8 A, number of positions: 4, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, color: light gray, contact surface: Tin
Your advantages
Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceAllows connection of two conductorsKey Commercial Data
Orderkey 1705910
Packing unit 1

GTIN 4046356807470
Custom tariff number 85366990
General
Range of articles MCVR 1,5/..-ST
Type of contact Female connector
Number of positions 4
Connection method Screw connection with tension sleeve
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²
Conductor cross section AWG min. 28
Conductor cross section AWG max. 16
2 conductors with same cross section, solid min. 0.08 mm²
2 conductors with same cross section, solid max. 0.5 mm²
2 conductors with same cross section, stranded min. 0.08 mm²
2 conductors with same....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCVR 1,5/ 4-ST-3,81KMGYBD:1-4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.