INDUSTRIAL COMPONENT DATA

MCVW 1,5/ 4-ST-3,5BD:X11/4-1SO 1003182 PHOENIX CONTACT Connector for printed circuit board, number of poles:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCVW 1,5/ 4-ST-3,5BD:X11/4-1SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCVW 1,5/ 4-ST-3,5BD:X11/4-1SO
Catalog number	1003182
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-D62587A996
Generated	2026-11-19

Product Overview

Connector for printed circuit board, number of poles: 4, pitch: 3.5 mm, type of connection: Connection by screw with capsule-wheel drive, color: green, surface contacts: Tin
Connector for printed circuit board, nominal section: 1.5 mm², color: green, rated current: 8 A, dimensioning voltage (III/2): 160 V, surface contacts: Tin, contact type: Connection female, Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, number of connections: 4, article family: MCVW 1.5/.. -ST, pitch: 3.5 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: -90 °,Stecksystem: MINI COMBICON, Lock: without, type of packaging: packed in box
PCB connector, nominal cross section: 1.5 mm2, color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Socket, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: MCVW 1,5/..-ST, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: -90 °, plug-in system: COMBICON MC 1,5, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Connectors S
Product type PCB connector

Product family MCVW 1,5/..-ST
Number of positions 4
Pitch 3.5 mm
Number of connections 4
Number of rows 1
Number of potentials 4
Electrical propertiesNominal current IN 8 A
Nominal voltage UN 160 V
Degree of pollution 3
Contact resistance 3.5 m?
Rated voltage (III/3) 160 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 320 V
Rated surge voltage (II/2) 2.5 kV
Connection dataConnection technology
Type Standard
Connector system COMBICON MC 1,5
Nominal cross section 1.5 mm²
Contact connection type Socket
Interlock
Locking type without
Mounting flange without
Conductor connection
Connection method Screw connection with tension sleeve
Conductor/PCB connection direction -90 °
Conductor cross section rigid 0.14 mm² ... 1.5 mm²
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section AWG 28 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.5 mm²
2 conductors with same cross section, solid 0.08 mm² ... 0.5 mm²
2 conductors with same cross section, flexible 0.08 mm² ... 0.75 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.34 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCVW 1,5/ 4-ST-3,5BD:X11/4-1SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.