INDUSTRIAL COMPONENT DATA

ME 22,5-KIT-MSTBO-7035+4PSPT4 1343036 PHOENIX CONTACT DIN rail box, for DIN rail mounting, closed housing to..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5-KIT-MSTBO-7035+4PSPT4



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5-KIT-MSTBO-7035+4PSPT4
Catalog number	1343036
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-A3B9EAF667
Generated	2026-11-19

Product Overview

DIN rail box, for DIN rail mounting, closed housing top, color: light gray (similar RAL 7035), width: 22.6 mm, height: 99 mm, depth: 113.65 mm, incl. 4 pcs of PCB connectors, 4 poles, push-in spring connection, for 2.5 mm2, rated current: 12 A, 320 V, Printed circuit board surface: 7800 mm2
Rail housing, for DIN rail mounting, top of closed housing, colour: luminous grey (7035), width: 22.6 mm, height: 99 mm, depth: 113.65 mm, incl. 4 PCB connector units, 4 poles, push-in spring connection, for 2.5 mm², nominal current: 12 A, 320 V, printed circuit board surface: 7800 mm²
DIN rail housing, for mounting on a DIN rail, closed upper housing part, color: light grey (7035), width: 22.6 mm, height: 99 mm, depth: 113.65 mm, incl. 4 PCB connectors, 4-pos., Push-in spring connection, for 2.5 mm2, nominal current: 12 A, 320 V, PCB surface: 7800 mm2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT

Additional Product Information

Technical dataNotesGeneral Please observe the assembly instructions available in the download area.
General Material of contact pads for bus connector, galvanic gold (hard gold)
General The PCB surface specification is for orientation purposes and is based on a basic PCB. The housing can also accommodate several PCBs.
Product propertiesProduct type Stackable housing set

Product family ME 22,5
Number of positions 16
Max. number of positions 16 (pitch: 5 mm)
Number of rows 2
Type for mounting on a DIN rail, closed upper housing part
incl. 4 PCB connectors, 4-pos., Push-in spring connection, for 2.5 mm², nominal current: 12 A, 320 V
Housing type DIN rail housing
Ventilation openings present yes
Housing series ME
Connection dataConnection method Push-in spring connection
DimensionsDimensional drawing
Width 22.6 mm
Height 99 mm
Depth 113.65 mm
Depth from top edge of DIN rail 107 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor light grey (7035)
Flammability rating according to UL 94 V0
Surface characteristics untreated
Housing material Polyamide
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) max. 80 %
PCB dataNumber of PCB holders 1
Type of PCB mount Latching
Total PCB surface 7800 mm²
Thickness...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5-KIT-MSTBO-7035+4PSPT4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.