INDUSTRIAL COMPONENT DATA

ME 22,5 OT-1MSTBO KMGY S1390 1110784 PHOENIX CONTACT DIN rail housing, Upper housing part for connectors wit..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 OT-1MSTBO KMGY S1390

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 OT-1MSTBO KMGY S1390
Catalog number	1110784
Category	Electronic enclosure
Minimum order	50 Pcs
Document ID	EO-CD80C1BD3D
Generated	2026-11-19

Product Overview

DIN rail housing, Upper housing part for connectors with header, width: 22.6 mm, height: 99 mm, depth: 45.85 mm, color: light gray (7035)
Rail housing, Top of the connector housing with base housing, width: 22.6 mm, height: 99 mm, depth: 45.85 mm, color: light gray (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1110784
Packing unit 1
GTIN 4063151025274
Custom tariff number 85389099
Item properties
Material data
PCB data
Vibration test
Thermostability (Ball Thrust Test)

Degrees of protection provided by housings (IP code)
Packaging information
Classifications
Dimensions
Ambient conditions
Mechanical strength/tumbling barrel
Shock
Test for assessing the risk of fire (glow wire)
General information
Standards and regulations
Item properties
Brief article description Upper part of housing
Type ME 22,5 OT-1MSTBO KMGY S1390
Order No. 1110784
Housing type DIN rail housing
Type Upper housing part for connectors with header
Max. IP code to attain IP20
Mounting type Latching with lower housing part
Number of levels 1
Connection levels 1 (Single-sided)
Max. number of positions 5 (pitch: 3.5 mm)
4 (pitch: 5 mm)
3 (pitch: 7.25 mm)
Back to topDimensions
Width [w] 22.6 mm
Height [h] 99 mm
Depth [d] 45.85 mm
Depth from base support surface [d] 38.5 mm
Back to topMaterial data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topPCB data
Number of PCB holders 1
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Back to topMechan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 OT-1MSTBO KMGY S1390 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.