INDUSTRIAL COMPONENT DATA

ME 22,5 OT-MKDSO RD 2853365 PHOENIX CONTACT Upper part of housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 OT-MKDSO RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 OT-MKDSO RD
Catalog number	2853365
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-0D51713638
Generated	2026-11-19

Product Overview

Upper part of housing
Rail housing, Top of the terminal housing for printed circuit board with screw connection, width: 22.6 mm, height: 99 mm, depth: 45.85 mm, color: red (3001)
DIN rail housing, Upper housing part for PCB terminal blocks with screw connection, width: 22.6 mm, height: 99 mm, depth: 45.85 mm, color: red (similar RAL 3001)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataProduct propertiesProduct type Upper housing part
Housing type DIN rail housing
Housing series ME
Product family ME 22,5..
Number of positions 16
Max. number of positions 20 (pitch: 3.5 mm)
16 (pitch: 5 mm)
Type Upper housing part for PCB terminal blocks with screw connection
Ventilation openings present no
Data management status
Article revision 02

DimensionsDimensional drawing
Width 22.6 mm
Height 99 mm
Depth 45.85 mm
Depth from base support surface 38.5 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor (Housing) red (RAL 3001)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsVibration test
Specification IEC 60068-2-6:2007-12
Frequency 10 - 150 - 10 Hz
Sweep speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 2g (58.1 Hz ... 150 Hz)
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis
Glow-wire test
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Thermal stability / ball thrust test
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20 N
Mechanical strength / tumbling barrel
Specification IEC 60998-1:2002-12
Height of fall 50 cm
Frequency 10
Shocks
Specification IEC 60068-2-27:2008-02
Pulse shape Half-sine
Acceleration 15g
Shock duration 11 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Deg...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 OT-MKDSO RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.