INDUSTRIAL COMPONENT DATA

ME 22,5 UT/FE BUS 2P+10 GY 2203506 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot catc..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 UT/FE BUS 2P+10 GY

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 UT/FE BUS 2P+10 GY
Catalog number	2203506
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-F99DE75ADC
Generated	2026-11-19

Product Overview

DIN rail housing, Lower housing part with metal foot catch, tall design, with vents, width: 22.6 mm, height: 99 mm, depth: 107.3 mm
Rail box, Bottom of the box with metal pin, with FE contact, high design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 107.3 mm, color: gray (7042), cross bridge: integrated bus connector, number of poles cross connector: 2+10, Bus connector: 2 parallel contacts, 10 series contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203506
Packing unit 1
GTIN 4055626622460
Custom tariff number 85389099
Item properties
Material data
PCB data
Power dissipation, single housing at 30 °C
Power dissipation, single housing at 50 °C
Mechanical strength/tumbling barrel

Shock
Test for assessing the risk of fire (glow wire)
General information
Standards and regulations
Dimensions
Ambient conditions
Power dissipation, single housing at 20 °C
Power dissipation, single housing at 40 °C
Power dissipation, single housing at 60 °C
Vibration test
Thermostability (Ball Thrust Test)
Degrees of protection provided by housings (IP code)
Packaging information
Classifications
Item properties
Brief article description Mounting base housing
Type ME 22,5 UT/FE BUS 2P+10 GY
Order No. 2203506
Housing type DIN rail housing
Type Lower housing part with metal foot catch, tall design
Max. IP code to attain IP20
Mounting type DIN rail mounting
Ventilation openings present yes
Back to topDimensions
Width [w] 22.6 mm
Height [h] 99 mm
Depth [d] 107.3 mm
Depth from top edge of DIN rail [d] 99.8 mm
Depth from top edge of DIN rail to support point on upper part [d] 68.5 mm
Back to topMaterial data
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (stora...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 UT/FE BUS 2P+10 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.