INDUSTRIAL COMPONENT DATA

ME 22,5 UT/FE BUS/ 5 KMGY 2914071 PHOENIX CONTACT Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 UT/FE BUS/ 5 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 UT/FE BUS/ 5 KMGY
Catalog number	2914071
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-87161E6D2B
Generated	2026-11-19

Product Overview

Mounting base housing
Rail box, Bottom of the box with metal pin, with FE contact, high design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 107.3 mm, color: light gray (7035), cross bridge: integrated bus connector, number of poles cross connector: 5, Bus connector: 5 contacts in parallel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2914071
Packing unit 10 pc
Note Made to Order (non-returnable)
GTIN 4017918950224
Weight per Piece (excluding packing) 38.520 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Housing type Component housing
Housing material Polyamide
Color (RAL) light gray (7035)

Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Dimensions
Length 99 mm
Height 114.5 mm
Width 22.5 mm
Depth 99 mm
102 mm
Technical data
Connection in acc. with standard CUL
Nominal voltage UN 300 V
Nominal current IN 8 A
Indicator1 CUL1
Power dissipation without gap 6.1 W
Power dissipation with 20 mm gap 12.1 W
Number of positions 16
24
24
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC 13.231261501

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 UT/FE BUS/ 5 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.