INDUSTRIAL COMPONENT DATA

ME 22,5 UT/FE GY 1109642 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot catch, tall de..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 UT/FE GY

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 22,5 UT/FE GY
Catalog number	1109642
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-CC0EF8E1C8
Generated	2026-11-19

Product Overview

DIN rail housing, Lower housing part with metal foot catch, tall design, width: 22.5 mm
Rail box, Bottom of the box with metal pin, with FE contact, high design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 107.3 mm, color: gray (7042), cross bridge: without bus connector, number of poles cross connector: not relevant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1109642
Packing unit 1
GTIN 4063151020163
Custom tariff number 85389099
Item properties
Material data
PCB data
Power dissipation, single housing at 30 °C
Power dissipation, single housing at 50 °C
Mechanical strength/tumbling barrel
Shock

Test for assessing the risk of fire (glow wire)
Packaging information
Classifications
Dimensions
Ambient conditions
Power dissipation, single housing at 20 °C
Power dissipation, single housing at 40 °C
Power dissipation, single housing at 60 °C
Vibration test
Thermostability (Ball Thrust Test)
Degrees of protection provided by housings (IP code)
Standards and regulations
Item properties
Brief article description Mounting base housing
Type ME 22,5 UT/FE GY
Order No. 1109642
Housing type DIN rail housing
Type Lower housing part with metal foot catch, tall design
Back to topDimensions
Width [w] 22.5 mm
Back to topMaterial data
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topPCB data
Type of PCB mount Latching
Back to topPower dissipation, single housing at 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 6.1 W
Back to topPower dissipation, single housing at 30 °C
Ambient temperat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 UT/FE GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.