INDUSTRIAL COMPONENT DATA

# ME 35 UT/FE BUS/10 GN 2713081 PHOENIX CONTACT Mounting base housing

**Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 35 UT/FE BUS/10 GN**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | ME 35 UT/FE BUS/10 GN |
| Catalog number | 2713081 |
| Category | Extruded profile modular housing |
| Minimum order | 10 Pcs |
| Document ID | EO-20066E22B8 |
| Generated | 2026-11-19 |

## Product Overview

Mounting base housing
Rail box, Lower part of the housing with metal pin, with 2 FE contacts, high design, with ventilation slits, width: 35.2 mm, height: 99 mm, depth: 107.3 mm, color: green (6021), cross bridge: integrated bus connector, number of poles cross connector: 10, Bus connector: 10 parallel contacts

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Key Commercial Data
Orderkey 2713081
Packing unit 10 pc
GTIN 4017918909642
Weight per Piece (excluding packing) 75.100 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Housing type Component housing
Housing material Polyamide
Color (RAL) green (6021)
Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Dimensions
Length 99 mm
Height 114.5 mm
Width 35 mm
Depth 99 mm
Technical data
Connection in acc. with standard CUL
Nominal voltage UN 300 V
Nominal current IN 8 A
Indicator1 CUL1
Power dissipation without gap 7.9 W
Power dissipation with 20 mm gap 16.3 W
Number of positions 24
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC 13.231261501

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 35 UT/FE BUS/10 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.