INDUSTRIAL COMPONENT DATA

# ME 35 UT/FE BUS/10+2 BK 2200400 PHOENIX CONTACT Component housing, length: 99 mm, with vents, Lower part, Cr..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 35 UT/FE BUS/10+2 BK**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | ME 35 UT/FE BUS/10+2 BK |
| Catalog number | 2200400 |
| Category | Extruded profile modular housing |
| Minimum order | 100 Pcs |
| Document ID | EO-F1AF25BB1C |
| Generated | 2026-11-19 |

## Product Overview

Component housing, length: 99 mm, with vents, Lower part, Cross connection: integrated bus connector, color: black, width: 35 mm, height: 114.5 mm, number of positions cross connector: 10+2
Rail box, Lower part of the housing with metal pin, with 2 FE contacts, high design, with ventilation slits, width: 35.2 mm, height: 99 mm, depth: 107.3 mm, color: black (9005), cross bridge: integrated bus connector, number of poles cross connector: 10+2, Bus connector: 10 parallel contacts, 2 series contacts

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Component housing, length: 99 mm, with vents, Lower part, Cross connection: integrated bus connector, color: black, width: 35 mm, height: 114.5 mm, number of positions cross connector: 10+2
Key Commercial Data
Orderkey 2200400
Packing unit 1
GTIN 4046356570176
Custom tariff number 85369010
General
Housing type Component housing

Housing material Polyamide
Color (RAL) black
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C (depending on power dissipation)
Dimensions
Length 99 mm
Height 114.5 mm
Width 35 mm
Depth 99 mm
Technical data
Power dissipation without gap 7.9 W
Power dissipation with 20 mm gap 16.3 W
Number of positions 24
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss
eCl@ss 4.0 27180401
eCl@ss 4.1 27180401
eCl@ss 5.0 27180505
eCl@ss 5.1 27180500
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
ETIM
ETIM 2.0 EC001031
ETIM 3.0 EC001031
ETIM 4.0 EC001031
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
UNSPSC
UNSPSC 6.01 31261501
UNSPSC 7.0901 31261501
UNSPSC 11 31261501
UNSPSC 12.01 31261501
UNSPSC 13.2 31261501

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 35 UT/FE BUS/10+2 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.