INDUSTRIAL COMPONENT DATA

ME 52,5 UT/FE BUS/10+2 GN 2278209 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot catch..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 52,5 UT/FE BUS/10+2 GN

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 52,5 UT/FE BUS/10+2 GN
Catalog number	2278209
Category	Extruded profile modular housing
Minimum order	250 Pcs
Document ID	EO-288B2B0E6C
Generated	2026-11-19

Product Overview

DIN rail housing, Lower housing part with metal foot catch, tall design, with vents, width: 52.5 mm, height: 99 mm, depth: 107.3 mm, cross connection: integrated bus connector, number of positions cross connector: 10+2, color: green (6021) Rail box, Bottom of the box with metal pin, with FE contact, high design, with ventilation slits, width: 52.5 mm, height: 99 mm, depth: 107.3 mm, color: green (Similar RAL 6021), cross bridge: integrated bus connector, number of poles cross connector: 10+2, Bus connector: 10 parallel contacts, 2 series contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2278209
Packing unit 1
GTIN 4046356326124
Custom tariff number 85369010
Item properties
Material data
PCB data
Packaging information
Environmental Product Compliance
Dimensions

Ambient conditions
General information
Standards and regulations
Classifications
Item properties
Brief article description Mounting base housing
Type ME 52,5 UT/FE BUS/10+2 GN
Order No. 2278209
Housing type DIN rail housing
Type Lower housing part with metal foot catch, tall design
Max. IP code to attain IP20
Mounting type DIN rail mounting
Ventilation openings present yes
Back to topDimensions
Width [w] 52.5 mm
Height [h] 99 mm
Depth [d] 107.3 mm
Depth from top edge of DIN rail [d] 99.8 mm
Depth from top edge of DIN rail to support point on upper part [d] 68.5 mm
Back to topMaterial data
Color (RAL) green (6021)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topPCB data
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Type of note Recommendation
Note Material of contact pads for bus connector, galvanic gold (hard gold)
Ba...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 52,5 UT/FE BUS/10+2 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.