INDUSTRIAL COMPONENT DATA

ME 67,5 UTG/FE KMGY 1005094 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot catch, tall..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 67,5 UTG/FE KMGY

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 67,5 UTG/FE KMGY
Catalog number	1005094
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-F8498B83B5
Generated	2026-11-19

Product Overview

DIN rail housing, Lower housing part with metal foot catch, tall design, without vents, width: 67.8 mm, height: 99 mm, depth: 107.3 mm, color: light gray (7035)
Rail box, Bottom of the box with metal pin, with 3 FE contacts, high design, without ventilation slits, width: 67.8 mm, height: 99 mm, depth: 107.3 mm, color: light gray (7035), cross bridge: without bus connector, number of poles cross connector: not relevant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1005094
Packing unit 1
GTIN 4055626474960
Custom tariff number 85472000
Item properties
Material data
PCB data
Packaging information
Classifications
Dimensions

Ambient conditions
General information
Standards and regulations
Item properties
Brief article description Mounting base housing
Type ME 67,5 UTG/FE KMGY
Order No. 1005094
Housing type DIN rail housing
Type Lower housing part with metal foot catch, tall design
Max. IP code to attain IP20
Mounting type DIN rail mounting
Ventilation openings present no
Back to topDimensions
Width [w] 67.8 mm
Height [h] 99 mm
Depth [d] 107.3 mm
Depth from top edge of DIN rail [d] 99.8 mm
Depth from top edge of DIN rail to support point on upper part [d] 68.5 mm
Back to topMaterial data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topPCB data
Number of PCB holders 3
PCB thickness 1.4 mm ... 1.8 mm
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Type of note Recommendation
Note Material of contact pads for bus connector, galvani...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 67,5 UTG/FE KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.