INDUSTRIAL COMPONENT DATA

ME 90 UT/12FE TBUS BU S1364 1098972 PHOENIX CONTACT DIN rail housing, Lower housing part with metal foot cat..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 90 UT/12FE TBUS BU S1364

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 90 UT/12FE TBUS BU S1364
Catalog number	1098972
Category	Electronic enclosure
Minimum order	50 Pcs
Document ID	EO-C698B3A4C5
Generated	2026-11-19

Product Overview

DIN rail housing, Lower housing part with metal foot catch, tall design, with vents, width: 90.4 mm, height: 99 mm, depth: 107.3 mm, cross connection: DIN rail connector (optional), color: blue (5015)
Rail box, Bottom of the box with metal pin, with FE contact, high design, with ventilation slits, width: 90.4 mm, height: 99 mm, depth: 107.3 mm, color: blue (5015), cross bridge: Bus connector for rail (optional), number of poles cross connector: 5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1098972
Packing unit 1
GTIN 4055626945538
Custom tariff number 85389099
Item properties
Material data
PCB data
Packaging information
Classifications
Dimensions
Ambient conditions

General information
Standards and regulations
Item properties
Brief article description Mounting base housing
Type ME 90 UT/12FE TBUS BU S1364
Order No. 1098972
Housing type DIN rail housing
Type Lower housing part with metal foot catch, tall design
Max. IP code to attain IP20
Mounting type DIN rail mounting
Ventilation openings present yes
Back to topDimensions
Width [w] 90.4 mm
Height [h] 99 mm
Depth [d] 107.3 mm
Depth from top edge of DIN rail [d] 99.8 mm
Depth from top edge of DIN rail to support point on upper part [d] 68.5 mm
Back to topMaterial data
Color (RAL) blue (5015)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topPCB data
Number of PCB holders 4
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Type of note Recommendation
Note Material of contact pads for bus connector, galvanic gold (hard gold)
Back to to...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 90 UT/12FE TBUS BU S1364 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.