
INDUSTRIAL COMPONENT DATA

ME-IO 75,2 B 10U TBUS 7035 2202664 PHOENIX CONTACT Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME-IO 75,2 B 10U TBUS 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME-IO 75,2 B 10U TBUS 7035
Catalog number	2202664
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-97DA6CC086
Generated	2026-11-19

Product Overview

Mounting base housing
Rail housing, Lower part of housing with metal pin, with ventilation slits, width: 75.87 mm, height: 120.6 mm, depth: 64.3 mm, colour: light grey (7035), cross bridge: Rail bus connector (optional), number of poles cross connector: 5 or 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2202664
Packing unit 10 pc
Minimum order quantity 10 pc
GTIN 4055626199306
Weight per Piece (excluding packing) 70.760 g
Custom tariff number 85472000
Country of origin DE (Germany)
Item properties
Brief article description Mounting base housing
Type ME-IO 75,2 B 10U TBUS 7035
Order No. 2202664
Housing type Component housing

Type Lower part
Max. IP code to attain IP20
Mounting type DIN rail mounting
Ventilation openings present yes
Max. number of positions 192 (pitch: 3.45 mm)
128 (pitch: 5 mm)
Dimensions
Width [w] 75.9 mm
Height [h] 120.6 mm
Depth [d] 64.3 mm
Depth from top edge of DIN rail [d] 57.7 mm
Material data
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material Polyamide
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
PCB data
PCB thickness 1.4 mm ... 1.8 mm
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Packaging information
Type of packaging packed in cardboard
Pieces per package 10
Denomination packing units Pcs.
Outer packaging type Carton
Standards and regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classification...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME-IO 75,2 B 10U TBUS 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.