INDUSTRIAL COMPONENT DATA

ME MAX 17,5 2-2 BU 1129107 PHOENIX CONTACT DIN rail housing, Complete housing with metal foot catch, tall de..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 17,5 2-2 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 17,5 2-2 BU
Catalog number	1129107
Category	Electronic enclosure
Minimum order	100 Pcs
Document ID	EO-9972BDBDF6
Generated	2026-11-19

Product Overview

DIN rail housing, Complete housing with metal foot catch, tall design, with vents, width: 17.5 mm, height: 99 mm, depth: 114.5 mm, color: blue (5015)
Rail box, Full housing with metal pin, tall design, with ventilation slits, width: 17.6 mm, height: 99 mm, depth: 113.65 mm, color: blue (5015), cross bridge: Rail bus connector (optional), number of poles cross connector: 5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1129107
Packing unit 1
GTIN 4063151056766
Custom tariff number 85389099
Drawings
Dimensions
Ambient conditions
General information
Standards and regulations
Item properties
Material data

PCB data
Packaging information
Classifications
Drawings
Dimensional drawing
Back to topItem properties
Brief article description Electronic housing
Type ME MAX 17,5 2-2 BU
Order No. 1129107
Housing type DIN rail housing
Type Complete housing with metal foot catch, tall design
Max. IP code to attain IP20
Mounting type DIN rail mounting
Number of levels 2
Connection levels 2 (Both sides)
Ventilation openings present yes
Max. number of positions 16 (pitch: 3.5 mm)
12 (pitch: 5 mm)
8 (pitch: 7.25 mm/7.5 mm)
Back to topDimensions
Dimensional drawing
Width [w] 17.5 mm
Height [h] 99 mm
Depth [d] 114.5 mm
Depth from top edge of DIN rail [d] 107 mm
Back to topMaterial data
Color (RAL) blue (5015)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topPCB data
Number of PCB holders 1
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download are...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 17,5 2-2 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.