INDUSTRIAL COMPONENT DATA

ME MAX 17,5 GEH-R CL G3-3 PGBU 2203941 PHOENIX CONTACT DIN rail housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 17,5 GEH-R CL G3-3 PGBU

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 17,5 GEH-R CL G3-3 PGBU
Catalog number	2203941
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-38409C2A80
Generated	2026-11-18

Product Overview

DIN rail housing
Rail housing, Housing half-frame (right), tall design, no ventilation slits, width: 11.3 mm, height: 99 mm, depth: 112.85 mm, colour: columbian blue (similar RAL 5014), transverse bridge: rail bus connector (optional)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203941
Packing unit 1
GTIN 4055626460529
Custom tariff number 85389099
Item properties
Ambient conditions
General information
Standards and regulations
Material data
PCB data
Packaging information
Classifications

Item properties
Brief article description Housing half shell
Type ME MAX 17,5 GEH-R CL G3-3 PGBU
Order No. 2203941
Housing type DIN rail housing
Type
Max. IP code to attain IP20
Mounting type DIN rail mounting
Back to topMaterial data
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topPCB data
Mounting position Vertical (horizontal DIN rail)
Type of PCB mount Latching
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Type of note Recommendation
Note Material of contact pads for bus connector, galvanic gold (hard gold)
Back to topPackaging information
Pieces per package 50
Denomination packing units Pcs.
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 17,5 GEH-R CL G3-3 PGBU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.