INDUSTRIAL COMPONENT DATA

ME MAX 22,5 2-2 DEV-KIT KMGY 2202524 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 22,5 2-2 DEV-KIT KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 22,5 2-2 DEV-KIT KMGY
Catalog number	2202524
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-BACD6FDFAE
Generated	2026-11-18

Product Overview

Electronic housing
DEV-KIT ME MAX: includes 1 ME MAX 22.5 2-2 housing and plug-in connection technology (4x MSTBO with 4x MSTBT), supplied in individual pieces
DEV-KIT ME MAX: contains 1 x ME MAX 22,5 2-2 housing and pluggable connection technology (4x MSTBO with 4x MSTBT), supplied in individual parts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.
Recommendation Material of contact pads for bus connector, galvanic gold (hard gold)
Product propertiesProduct type Stackable housing set
Housing type DIN rail housing
Housing series ME-MAX
Product family ME MAX.. 2-2
Max. number of positions 16 (pitch: 5 mm)
Number of rows 2
Type Set consisting of upper housing part and connection technology
Ventilation openings present yes
Data management status

Article revision 04
DimensionsDimensional drawing
Width 22.6 mm
Height 99 mm
Depth 113.65 mm
Depth from top edge of DIN rail 107 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor (Housing) light gray (RAL 7035)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
PCB dataType of PCB mount Latching
Thickness of the PCB 1.4 mm ... 1.8 mm
MountingMounting type DIN rail mounting

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 22,5 2-2 DEV-KIT KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.