INDUSTRIAL COMPONENT DATA

# ME MAX 22,5 3-3 BU 2201117 PHOENIX CONTACT DIN rail housing, Tall design, with vents, width: 22.5 mm, Cross ..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 22,5 3-3 BU**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | ME MAX 22,5 3-3 BU |
| Catalog number | 2201117 |
| Category | Electronic enclosure |
| Minimum order | 200 Pcs |
| Document ID | EO-9472EC13D6 |
| Generated | 2026-11-19 |

## Product Overview

DIN rail housing, Tall design, with vents, width: 22.5 mm, Cross connection: DIN rail bus connector, color: blue (5015), number of positions cross connector: 5
Rail box, Full housing with metal pin, high design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 113.65 mm, color: blue (5015), cross bridge: Bus connector for rail (optional), number of poles cross connector: 5

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

DIN rail housing, Tall design, with vents, width: 22.5 mm, Cross connection: DIN rail bus connector, color: blue (5015), number of positions cross connector: 5
Key Commercial Data
Orderkey 2201117
Packing unit 1
GTIN 4046356725873
Custom tariff number 85389099
General
Housing type DIN rail housing
Housing material Polyamide
Color (RAL) blue (5015)
Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Dimensions
Width 22.5 mm
Height 99 mm
Depth 114.5 mm
Technical data
Number of positions 18
30
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss
eCl@ss 4.0 27180401
eCl@ss 4.1 27180401
eCl@ss 5.0 27180401
eCl@ss 5.1 27180400
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
ETIM
ETIM 2.0 EC001031
ETIM 3.0 EC001031
ETIM 4.0 EC002643
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
UNSPSC
UNSPSC 6.01 31261501
UNSPSC 7.0901 31261501
UNSPSC 11 31261501
UNSPSC 12.01 31261501
UNSPSC 13.2 31261501

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 22,5 3-3 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.