INDUSTRIAL COMPONENT DATA

ME MAX 35 3-3 BK 1105020 PHOENIX CONTACT DIN rail housing, cross connection: DIN rail bus connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 35 3-3 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 35 3-3 BK
Catalog number	1105020
Category	Electronic enclosure
Minimum order	500 Pcs
Document ID	EO-82FB44710C
Generated	2026-11-18

Product Overview

DIN rail housing, cross connection: DIN rail bus connector
Rail housing, Full housing with metal pin, high design, with ventilation slits, width: 35.2 mm, height: 99 mm, depth: 113.65 mm, color: black (9005), cross bridge: Rail bus connector (optional), number of poles cross connector: 5
DIN rail housing, Complete housing with metal foot catch, tall design, with vents, width: 35.2 mm, height: 99 mm, depth: 113.65 mm, color: black (similar RAL 9005), cross connection: DIN rail connector (optional), number of positions cross connector: 5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.
Recommendation Material of contact pads for bus connector, galvanic gold (hard gold)
Product propertiesProduct type Complete housing
Housing type DIN rail housing
Housing series ME-MAX
Product family ME MAX 35..
Max. number of positions 48 (pitch: 3.5 mm)
36 (pitch: 5 mm)
24 (pitch: 7.25 mm/7.5 mm)
Number of rows 3

3
Type Complete housing with metal foot catch, tall design
Ventilation openings present yes
Data management status
Article revision 00
DimensionsDimensional drawing
Width 35.2 mm
Height 99 mm
Depth 113.65 mm
Depth from top edge of DIN rail 107 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor (Housing) black (RAL 9005)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsPower dissipation single housing for 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 7.9 W
Power dissipation single housing for 30 °C
Ambient temperature 30 °C
Reduction factor 0.91
Mounting position vertical
Power dissipation 7.2 W
Power dissipation single housing for 40 °C
Ambient temperature 40 °C
Reduction factor 0.81
Mounting position vertical
Power dissipation 6.4 W
Power dissipation single housing for 50 °C
Ambient temperature 50 °C
Reduction factor 0.7
Mounting position vertical
Power dissipation 5.5 W
Power d...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 35 3-3 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.