INDUSTRIAL COMPONENT DATA

ME MAX 45 MT 2-2 KMGY 2199647 PHOENIX CONTACT Components of electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 45 MT 2-2 KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 45 MT 2-2 KMGY
Catalog number	2199647
Category	Extruded profile modular housing
Minimum order	100 Pcs
Document ID	EO-CDD7C34FFF
Generated	2026-11-18

Product Overview

Components of electronic housing
Rail box, Middle element, tall design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 112.85 mm, colour: light grey (7035)
DIN rail housing, Intermediate element, tall design, with vents, width: 22.6 mm, height: 99 mm, depth: 112.85 mm, color: light gray (similar RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.
Product propertiesProduct type Complete housing center part
Housing type DIN rail housing
Housing series ME-MAX
Product family ME MAX 45..
Number of rows 2
Type Intermediate element, tall design
Ventilation openings present yes
Data management status
Article revision 00
DimensionsDimensional drawing

Width 22.6 mm
Height 99 mm
Depth 112.85 mm
Depth from top edge of DIN rail 107 mm
Material specificationsColor (Housing) light gray (RAL 7035)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) 80 %
PCB dataType of PCB mount Latching
MountingMounting type DIN rail mounting

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 45 MT 2-2 KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.