INDUSTRIAL COMPONENT DATA

ME MAX 67,5-KIT-U-U1-7035+3PSPT4 1342923 PHOENIX CONTACT Rail housing, for DIN rail mounting, colour: light ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 67,5-KIT-U-U1-7035+3PSPT4



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 67,5-KIT-U-U1-7035+3PSPT4
Catalog number	1342923
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-993F1F9A27
Generated	2026-11-19

Product Overview

Rail housing, for DIN rail mounting, colour: light grey (similar RAL 7035), width: 67.8 mm, height: 99 mm, depth: 113.65 mm, incl. 3 pcs of PCB connectors, 4 poles, screw connection, for 2.5 mm², rated current: 12 A, 320 V, PCB surface: 8300 mm² DIN rail housing, for mounting on a DIN rail, color: light grey (7035), width: 67.8 mm, height: 99 mm, depth: 113.65 mm, incl. 3 PCB connectors, 4-pos., screw connection, for 2.5 mm2, nominal current: 12 A, 320 V, PCB surface: 8300 mm2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT

Additional Product Information

Technical dataNotesGeneral Please observe the assembly instructions available in the download area.
General Material of contact pads for bus connector, galvanic gold (hard gold)
General The PCB surface specification is for orientation purposes and is based on a basic PCB. The housing can also accommodate several PCBs.
Product propertiesProduct type Stackable housing set
Number of positions 12
Max. number of positions 12 (pitch: 5 mm)
Number of rows 1
Type for mounting on a DIN rail
incl. 3 PCB connectors, 4-pos., screw connection, for 2.5 mm², nominal current: 12 A, 320 V
Housing type DIN rail housing
Ventilation openings present yes

Housing series ME-MAX
Connection dataConnection method Push-in spring connection
DimensionsDimensional drawing
Width 67.8 mm
Height 99 mm
Depth 113.65 mm
Depth from top edge of DIN rail 107 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor light grey (7035)
Flammability rating according to UL 94 V0
Surface characteristics untreated
Housing material Polyamide
Environmental and real-life conditionsAmbient conditions
Max. IP code to attain IP20
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) 80 % (maximum)
PCB dataNumber of PCB holders 3
Type of PCB mount Latching
Total PCB surface 8300 mm²
Thickness of the PCB 1.4 mm ... 1.8 mm
MountingMounting typ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 67,5-KIT-U-U1-7035+3PSPT4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.