INDUSTRIAL COMPONENT DATA

ME MAX B-22,5 YE S75 1030272 PHOENIX CONTACT DIN rail housing, Filler plug for unoccupied terminal points, w..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX B-22,5 YE S75



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX B-22,5 YE S75
Catalog number	1030272
Category	Electronic enclosure
Minimum order	100 Pcs
Document ID	EO-E6ADA8297A
Generated	2026-11-18

Product Overview

DIN rail housing, Filler plug for unoccupied terminal points, width: 20 mm, height: 21.6 mm, color: yellow (1018)
Rail box, Blank plug with ventilation slots for non-equipped terminal points, width: 20 mm, height: 21.6 mm, depth: 8.1 mm, colour: yellow (1018)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1030272
Packing unit 1
GTIN 4055626533599
Custom tariff number 39269097
Item properties
Material data
General information
Standards and regulations
Dimensions
Ambient conditions
Packaging information
Classifications

Item properties
Brief article description Filler plugs
Type ME MAX B-22,5 YE S75
Order No. 1030272
Housing type DIN rail housing
Type Filler plug for unoccupied terminal points
Mounting type Latching
Back to topDimensions
Width [w] 20 mm
Height [h] 21.6 mm
Back to topMaterial data
Color (RAL) yellow (1018)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Back to topPackaging information
Pieces per package 50
Denomination packing units Pcs.
Outer packaging type Resealable bag
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX B-22,5 YE S75 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.