INDUSTRIAL COMPONENT DATA

HC-M-KV-Z-M40 1646175 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-M-KV-Z-M40



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-M-KV-Z-M40
Catalog number	1646175
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-9AF617EDAC
Generated	2026-11-19

Product Overview

Cable gland
Metal cable gland with flange for compensated traction, thread length: 8 mm, cable sealing margin: 24-33 mm, clamping margin: 26-36 mm, SW 50, thread: M40

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1646175
Packing unit 10 pc
Catalog page Page 707 (C-2-2017)
GTIN 4017918941314
Weight per Piece (excluding packing) 268.460 g
Custom tariff number 74153300
Country of origin DE (Germany)
Dimensions
Length 49 mm
Length without connecting thread 41 mm
Connecting thread diameter 40 mm
Wrench size, union nut 52 mm
Wrench size, support 50 mm

Hexagon angular dimension 56 mm
Length of the connecting thread 8 mm
External cable diameter 24 mm ... 33 mm
Clamping range of the strain relief clip 26.00 mm ... 33.00 mm
Ambient conditions
Degree of protection (IP) IP65
Ambient temperature (operation) -20 °C ... 80 °C (static)
General
No. of conductors 1
Cable gland material Nickel-plated brass
Cable seal material Perbunan
O-ring material NBR
Shielded no
Thread type connection side M40 x 1.5
Thread type on connection side M40
Torque 18 Nm (Support sleeve)
12 Nm (Union nut)
Color silver
Standards and Regulations
Halogen-free no
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027141209eCl@ss 4.127141209eCl@ss 5.027149109eCl@ss 5.127149100eCl@ss 6.027149100eCl@ss 7.027149109eCl@ss 8.027149109eCl@ss 9.027144432
ETIM 2.0EC000441ETIM 3.0EC000441ETIM 4.0EC000441ETIM 5.0EC000441ETIM 6.0EC000441
UNSPSC 6.0130211808UNSPSC 7.090139121408UNSPSC 1139121408UNSPSC 12.0139121408UNSPSC 13.23912...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-M-KV-Z-M40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.