INDUSTRIAL COMPONENT DATA

MH-10CL-MULTI-55-PV-BK 1424584 PHOENIX CONTACT Cable feed-through plates

Brand: PHOENIX CONTACT | Manufacturer Part Number: MH-10CL-MULTI-55-PV-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MH-10CL-MULTI-55-PV-BK
Catalog number	1424584
Category	Mounting plate for cable support system
Minimum order	1 Pcs
Document ID	EO-0DCE795875
Generated	2026-11-18

Product Overview

Cable feed-through plates
Plates for cable passage, number of conductors: 10, outer diameter of the cable: 6x 2 mm ... 8mm, 2x 2mm... 18mm, 2x 2mm... 30 mm, material: PP (Core), material: TPE-SEBS (outer material), color: black, length: 154 mm, width: 56 mm, height: 20 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1424584
Packing unit 1 pc
Catalog page Page 690 (C-2-2017)
GTIN 4055626374871
Weight per Piece (excluding packing) 88.300 g
Custom tariff number 39269097
Country of origin FI (Finland)
Dimensions
Length 154 mm
Width 56 mm
Height 20 mm

Drill hole distance, horizontal 130 mm
Drill hole distance, vertical 32 mm
External cable diameter 6x 2 mm ... 8 mm
2x 2 mm ... 18 mm
2x 2 mm ... 30 mm
Ambient conditions
Degree of protection IP54
Ambient temperature (operation) -40 °C ... 90 °C
General
No. of conductors 10
Material TPE-SEBS
PP (Core)
TPE-SEBS (external material)
Flammability rating according to UL 94 V0
Color black
Note incl. mounting screws
Installation instructions M4 mounting screw, torque: 1.8 Nm, SW5 Allen key
The mounting screws provided are to be used for assembly.
Assembly sequence:
1) Attach the cable feed-through (Multigate) using the mounting screws provided (observe torque)
2) Pierce a hole in the membrane (using a screwdriver)
3) Guide the cable through the opening (from the outside)
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.123110102eCl@ss 6.027409200eCl@ss 7.027409208eCl@ss 8.027409208eCl@ss 9.027400569
ETIM 5.0EC001004

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MH-10CL-MULTI-55-PV-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.