INDUSTRIAL COMPONENT DATA

MINI MCR-2-UI-I-OLP 2902061 PHOENIX CONTACT Loop-powered isolators

Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI MCR-2-UI-I-OLP



Manufacturer	PHOENIX CONTACT
MPN / Reference	MINI MCR-2-UI-I-OLP
Catalog number	2902061
Category	Isolation amplifier
Minimum order	1 Pcs
Document ID	EO-4A2D8B97C8
Generated	2026-11-18

Product Overview

Loop-powered isolators
Loop-powered 2-way splitter with plug-in connection technology for galvanic separation of single-pole and bipolar analog signals. Input configurable via DIP switch. Screw connection technology, standard configuration.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2902061
Packing unit 1 pc
Catalog page Page 79 (C-5-2017)
GTIN 4046356652100
Weight per Piece (excluding packing) 107.900 g
Custom tariff number 85437090
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 6.2 mm
Height 110.5 mm

Depth 120.5 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Input data
Number of inputs 1
Configurable/programmable Yes
Voltage input signal 0 mV ... 1000 mV
0 mV ... 750 mV
0 mV ... 500 mV
0 mV ... 300 mV
0 mV ... 250 mV
0 mV ... 200 mV
0 mV ... 125 mV
0 mV ... 120 mV
0 mV ... 150 mV
0 mV ... 100 mV
0 mV ... 75 mV
0 mV ... 60 mV
0 mV ... 50 mV
0 V ... 10 V
0 V ... 7.5 V
0 V ... 5 V
0 V ... 3 V
0 V ... 2.5 V
0 V ... 2 V
0 V ... 1.5 V
0 V ... 1.25 V
0 V ... 1.2 V
0 V ... 30 V
0 V ... 25 V
0 V ... 20 V
0 V ... 12.5 V
0 V ... 12 V
0 V ... 15 V
-1000 mV ... 1000 mV
-750 mV ... 750 mV
-500 mV ... 500 mV
-300 mV ... 300 mV
-250 mV ... 250 mV
-200 mV ... 200 mV
-125 mV ... 125 mV
-120 mV ... 120 mV
-150 mV ... 150 mV
-100 mV ... 100 mV
-75 mV ... 75 mV
-60 mV ... 60 mV

-50 mV ... 50 mV
-10 V ... 10 V
-7.5 V ... 7.5 V
-5 V ... 5 V
-3 V ... 3 V
-2.5 V ... 2.5 V
-2 V ... 2 V
-1.25 V ... 1.25 V
-1.2 V ... 1.2 V
-1.5 V ... 1.5 V
-30 V ... 30 V
-25 V ... 25 V
-20 V ... 20 V
-12.5 V ... 12.5 V
-12 V ... 12 V
additional areas can be configured, see table
1 V .....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI MCR-2-UI-I-OLP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.