

INDUSTRIAL COMPONENT DATA

MK3DS 3/ 2-5,08 ABGY 1723386 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MK3DS 3/ 2-5,08 ABGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MK3DS 3/ 2-5,08 ABGY
Catalog number	1723386
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-C45BB908FD
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of rows: 3, number of poles per row: 2, article family: MK3DS 3, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: agate gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, number of solder pins per potential: 1, packaging type: boxed packaging. The item can be aligned with different numbers of poles!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1723386

Packing unit 50 pc

GTIN 4017918230791

Weight per Piece (excluding packing) 15.850 g

Custom tariff number 85472000

Country of origin DE (Germany)

Item properties

Number of positions 2

Drive form screw head Slotted (L)

Screw thread M3
Pin layout Linear pinning
Dimensions for the product
Length [l] 33.6 mm
Width [w] 12.7 mm
Height [h] 49.8 mm
Pitch 5.08 mm
Height (without solder pin) 44.8 mm
Solder pin [P] 5 mm
Dimension a 5.08 mm
Dimensions for PCB design
Hole diameter 1.3 mm
Packaging information
Type of packaging packed in cardboard
Pieces per package 50
Denomination packing units Pcs.
Standards and Regulations
Connection in acc. with standard EN-VDE
CSA
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.027141109eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss
7.027440401eCl@ss 8.027440401eCl@ss 9.027440401
ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643
UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC
13.239121432

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MK3DS 3/ 2-5,08 ABGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.