


INDUSTRIAL COMPONENT DATA

MKDS 1/14-3,5 GY NZ 2202390 1991477 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 1/14-3,5 GY NZ 2202390



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 1/14-3,5 GY NZ 2202390
Catalog number	1991477
Category	Printed circuit board terminal
Minimum order	40 Pcs
Document ID	EO-D11364F0EF
Generated	2026-09-28

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 200 V, nominal cross-section: 1.5 mm², number of potentials: 14, number of rows: 1, number of poles per row: 14, article family: MKDS 1, pitch: 3.5 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/PCB connection direction: 0°, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1991477

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918959210

Weight per Piece (excluding packing) 6.510 g

Custom tariff number 85369010

Country of origin DE (Germany)

Item properties

Brief article description PCB terminal block

Range of articles MKDS 1

Pitch 3.5 mm

Number of positions 14

Connection method Screw connection with tension sleeve

Drive form screw head Slotted (L)

Screw thread M2

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 1

Number of connections 14

Number of potentials 14

Electrical parameters

Rated current 13.5 A

Rated insulation voltage (III/2) 200 V

Rated surge voltage (III/2) 2.5 kV

Connection capacity

Conductor cross section solid 0.14 mm² ... 1.5 mm²

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

Conductor cross section AWG / kcmil 26 ... 16

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.5 mm²

2 conductors with same cross section, solid 0.14 mm² ... 0.5 mm²

2 conductors with same cross section, flexible 0.14 mm² ... 0.34 mm²

Stripping length 5 mm

Torque 0.22 Nm ... 0.25 Nm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Metal surface terminal point (top layer) Tin (5 - 7 µm Sn)

Metal surface terminal point (middle layer) Nickel (2 -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 1/14-3,5 GY NZ 2202390 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.