

## INDUSTRIAL COMPONENT DATA

# MKDS 1/ 3-3,81 BD:7-5 1706769 PHOENIX CONTACT Terminal block for printed circuit board, rated current: 10 A,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 1/ 3-3,81 BD:7-5



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | MKDS 1/ 3-3,81 BD:7-5          |
| Catalog number  | 1706769                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-FB6BC36AB4                  |
| Generated       | 2026-09-29                     |

## Product Overview

Terminal block for printed circuit board, rated current: 10 A, rated voltage: 200 V, pitch: 3.81 mm, number of poles: 3, connection type: Screw connection with traction capsule, mounting: Wave soldering, driver/printed circuit board connection direction: 0 °, color: green

Terminal block for printed circuit board, nominal current: 13.5 A, dimensioning voltage (III/2): 200 V, nominal section: 1.5 mm<sup>2</sup>, number of rows: 1, number of poles per row: 3, family of articles: MKDS 1, pitch: 3.81 mm, type of connection: Screw connection with traction capsule, screw clamping shape: L Longitudinal slot, Mounting: Wave soldering, conductor/PCB connection direction: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, number of soldering pins per potential: 1, packaging type: boxed

PCB terminal block, rated current: 17.5 A, sizing voltage (III/2): 200 V, nominal cross-section: 1.5 mm<sup>2</sup>, number of rows: 1, number of poles per row: 3, product series: MKDS 1, pitch: 3.81 mm, connection type: Screw connection with cage, screw connection form: L Longitudinal slot, mounting: Wave soldering, Conductor/board connection direction: 0°, Color: Green, Pin Layout: Linear Pinning, Pin Length [P]: 3.5mm, Number of Solder Pins per Potential: 1, Package Type: Packed in Carton

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

????? ????????

????????? ?????????? 48 ? AC

60 ? DC

???????? 5

??? ???????/????????? CANopen®

DeviceNet™

????? ?????????? >= 100

Environmental Product Compliance

China RoHS ?????? ?????? ?? ?????????? ?? ??????????: ?? ?????????? = EFUP-e

?? ????????? ??????? ???????, ?????????? ?? ??????? ?????????? ??????????

eCI@ss

eCI@ss 4.0 27060306

eCI@ss 4.1 27060306

eCI@ss 5.0 27061801

eCI@ss 5.1 27061801

eCI@ss 6.0 27061801

eCI@ss 7.0 27061801

eCI@ss 8.0 27279218

eCI@ss 9.0 27060311

ETIM

ETIM 3.0 EC001855

ETIM 4.0 EC001855

ETIM 5.0 EC001855

ETIM 6.0 EC001855

UNSPSC

UNSPSC 6.01 31251501

UNSPSC 7.0901 31251501

UNSPSC 11 31251501

UNSPSC 12.01 31251501

UNSPSC 13.2 31251501

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 1/ 3-3,81 BD:7-5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.