

INDUSTRIAL COMPONENT DATA

MKDS 3/14 CRWH 1714356 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 3/14 CRWH



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 3/14 CRWH
Catalog number	1714356
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-66FE8C0DB7
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal cross-section: 2.5 mm², number of potentials: 14, number of rows: 1, number of poles per row: 14, article family: MKDS 3, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: cream white, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, number of solder pins per potential: 1, packaging type: boxed packaging. The item can be aligned with different numbers of poles!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1714356

Packing unit 1

GTIN 4055626352688

Custom tariff number 85369010

Item properties

Brief article description PCB terminal block

Range of articles MKDS 3

Pitch 5 mm

Number of positions 14
Connection method Screw connection with tension sleeve
Screw thread M3
Mounting type Wave soldering
Pin layout Linear pinning
Number of levels 1
Number of connections 14
Number of potentials 14
Electrical parameters
Rated current 24 A
Rated insulation voltage (III/2) 400 V
Rated surge voltage (III/2) 4 kV
Connection capacity
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG / kcmil 24 ... 12
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with same cross section, solid 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 0.75 mm²
2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 1.5 mm²
Stripping length 8 mm
Torque 0.5 Nm ... 0.6 Nm
Material data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)
Metal....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 3/14 CRWH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.