

## INDUSTRIAL COMPONENT DATA

# MKDS 3/ 2 HT BK PIN3,5 1990371 PHOENIX CONTACT

## Terminal for printed circuit board, nominal current: 24 A, no..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 3/ 2 HT BK PIN3,5



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | MKDS 3/ 2 HT BK PIN3,5         |
| Catalog number  | 1990371                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-C4FA46CFF3                  |
| Generated       | 2026-09-29                     |

### Product Overview

Terminal for printed circuit board, nominal current: 24 A, nominal voltage: 320 V, pitch: 5 mm, number of poles: 2, type of connection: Connection by screw with capsule-traction, assembly: Soldering THR, direction for connection conductor/pcb: 0 °, color: black

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 320 V, nominal section: 2.5 mm<sup>2</sup>, number of potentials: 2, number of rows: 1, number of poles per row: 2, family of articles: MKDS 3/.. -HT, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping shape: L Longitudinal slot, mounting: Weld THR, conductor connection direction/printed circuit board: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, Packing Type: Boxed Packed

Printed circuit board terminal, nominal current: 24 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm<sup>2</sup>, number of potentials: 2, number of rows: 1, number of positions per row: 2, product range: MKDS 3/.. -HT, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, mounting: THR soldering / wave soldering, conductor/PCB connection direction: 0 °, color: black, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; PCB Connectors (PCC)

### Additional Product Information

Key Commercial Data

Orderkey 1990371

Packing unit 50 pc

Minimum order quantity 50 pc  
Note Made to Order (non-returnable)  
GTIN 4017918949983  
Weight per Piece (excluding packing) 3.770 g  
Custom tariff number 85369010  
Country of origin DE (Germany)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 3/ 2 HT BK PIN3,5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.