

**INDUSTRIAL COMPONENT DATA**

# MKDS 5/ 3-6,35 BK Z1L 1933600 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 5/ 3-6,35 BK Z1L



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | MKDS 5/ 3-6,35 BK Z1L          |
| Catalog number  | 1933600                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 1000 Pcs                       |
| Document ID     | EO-79C21AB2ED                  |
| Generated       | 2026-09-28                     |

## Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 32 A, rated voltage (III/2): 630 V, rated cross-section: 4 mm<sup>2</sup>, number of potentials: 3, number of rows: 1, number of poles per row: 3, article family: MKDS 5, pitch: 6.35 mm, connection type: Screw connection with traction capsule, screw clamping method: Z1L Pozidriv with longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 5.1 mm, number of solder pins per potential: 1, packaging type: boxed

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

## Additional Product Information

Key Commercial Data

Orderkey 1933600

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918888435

Weight per Piece (excluding packing) 7.760 g

Custom tariff number 85369010

Country of origin DE (Germany)

Item properties

Brief article description PCB terminal block

Range of articles MKDS 5

Pitch 6.35 mm

Number of positions 3

Connection method Screw connection with tension sleeve

Drive form screw head Slotted Pozidriv (Z1L)

Screw thread M3

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 1

Number of connections 3

Number of potentials 3

Electrical parameters

Rated current 32 A

Rated insulation voltage (III/2) 630 V

Rated surge voltage (III/2) 6 kV

Connection capacity

Conductor cross section solid 0.2 mm<sup>2</sup> ... 6 mm<sup>2</sup>

Conductor cross section flexible 0.2 mm<sup>2</sup> ... 4 mm<sup>2</sup>

Conductor cross section AWG / kcmil 24 ... 10

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 4 mm<sup>2</sup>

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 4 mm<sup>2</sup>

2 conductors with same cross section, solid 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>

2 conductors with same cross section, flexible 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

Stripping length 8 mm

Torque 0.5 Nm ... 0.6 Nm

Material data - contact

Note WEEE/RoHS-compliant, fr...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 5/ 3-6,35 BK Z1L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.