

INDUSTRIAL COMPONENT DATA

MKDS 5/ 6-6,35 GY 1026688 PHOENIX CONTACT Terminal for printed circuit board, rated voltage: 630 V, pitch: 6..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDS 5/ 6-6,35 GY

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDS 5/ 6-6,35 GY
Catalog number	1026688
Category	Printed circuit board terminal
Minimum order	500 Pcs
Document ID	EO-7AE3CDAD16
Generated	2026-09-29

Product Overview

Terminal for printed circuit board, rated voltage: 630 V, pitch: 6.35 mm, number of poles: 6, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: gray

Terminal block for printed circuit board, nominal current: 32 A, nominal voltage (III/2): 630 V, nominal section: 4 mm², number of potentials: 6, number of rows: 1, number of poles per row: 6, article family: MKDS 5, pitch: 6.35 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, Driver/PCB connection direction: 0°, Color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 5.1mm, number of solder pins per potential: 1, Packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDS 5/ 6-6,35 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.