

INDUSTRIAL COMPONENT DATA

MKDSL 1,5/ 8-5,08 1716607 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSL 1,5/ 8-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSL 1,5/ 8-5,08
Catalog number	1716607
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-3F737990B0
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 17.5 A, dimensioning voltage (III/2): 400 V, nominal section: 1.5 mm², Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, article family: MKDS 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, Connection direction conductor/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]:5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1716607

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918229191

Weight per Piece (excluding packing) 10.600 g

Custom tariff number 85369010

Country of origin DE (Germany)

Item properties

Brief article description PCB terminal block

Range of articles MKDS 1,5

Pitch 5.08 mm
Number of positions 8
Connection method Screw connection with tension sleeve
Drive form screw head Slotted (L)
Screw thread M3
Mounting type Wave soldering
Pin layout Linear pinning
Number of levels 1
Electrical parameters
Rated current 17.5 A
Rated insulation voltage (III/2) 400 V
Rated surge voltage (III/2) 4 kV
Connection capacity
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section AWG / kcmil 26 ... 14
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 1.5 mm²
2 conductors with same cross section, solid 0.14 mm² ... 1 mm²
2 conductors with same cross section, flexible 0.14 mm² ... 0.75 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 0.5 mm²
2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 1 mm²
Stripping length 7 mm
Torque 0.5 Nm ... 0.6 Nm
Material data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSL 1,5/ 8-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.