

INDUSTRIAL COMPONENT DATA

MKDSN 1,5/ 4 TS 1089246 PHOENIX CONTACT Terminal for printed circuit board, rated current: 13,5 A, pitch: 5 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 1,5/ 4 TS

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 1,5/ 4 TS
Catalog number	1089246
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-FB13DFF590
Generated	2026-09-26

Product Overview

Terminal for printed circuit board, rated current: 13,5 A, pitch: 5 mm, number of poles: 4, type of connection: Connection by screw with capsule-traction, assembly: Soldering by wave direction for connection conductor/pcb: 0 °, color: green

Terminal block for printed circuit board, nominal current: 13.5 A, dimensioning voltage (III/2): 400 V, nominal section: 1.5 mm², Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, family of articles: MKDSN 1.5, pitch: 5mm, type of connection: Screw connection with traction capsule, mounting: Wave soldering, Conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 1,5/ 4 TS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.