

INDUSTRIAL COMPONENT DATA

MKDSN 1,5/ 9 SSC 1715282 PHOENIX CONTACT PCB terminal block, pitch: 5 mm, number of positions: 9, color: gre..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 1,5/ 9 SSC



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 1,5/ 9 SSC
Catalog number	1715282
Category	Printed circuit board terminal
Minimum order	60 Pcs
Document ID	EO-085FCDEEA1
Generated	2026-09-29

Product Overview

PCB terminal block, pitch: 5 mm, number of positions: 9, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm
Terminal block for printed circuit board, rated current: 13.5 A, rated voltage (III/2): 400 V, rated cross-section: 1.5 mm²,
number of rows: 1, number of poles per row: 9, article family: MKDSN 1.5, pitch: 5 mm, connection type: Screw connection
with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: green, Pin
arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1715282

Packing unit 1

GTIN 4055626405285

Custom tariff number 85369010

Item properties

Dimensions for PCB design

Environmental Product Compliance

Dimensions for the product

Packaging information

Classifications

Item properties

Number of positions 9

Drive form screw head Slotted

Pin layout Linear pinning

[Back to top](#)Dimensions for the product

Length [l] 8.1 mm

Width [w] 45 mm

Height [h] 13.5 mm

Pitch 5 mm

Height (without solder pin) 10 mm

Solder pin [P] 3.5 mm

Pin spacing 5 mm

Dimension a 40 mm

[Back to top](#)Dimensions for PCB design

Hole diameter 1.3 mm

Pin spacing 5 mm

[Back to top](#)Packaging information

Type of packaging packed in cardboard

Pieces per package 100

Denomination packing units Pcs.

[Back to top](#)Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.1 27261100

eCl@ss 6.0 27261100

eCl@ss 7.0 27440401

eCl@ss 8.0 27440401

eCl@ss 9.0 27440401

[Back to top](#)ETIM

ETIM 5.0 EC002643

ETIM 6.0 EC002643

ETIM 7.0 EC002643

[Back to top](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 1,5/ 9 SSC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.