

INDUSTRIAL COMPONENT DATA

MKDSN 2,5/ 3-5,08 GY SZS 1021205 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 400 V, p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 2,5/ 3-5,08 GY SZS

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 2,5/ 3-5,08 GY SZS
Catalog number	1021205
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-A011509C11
Generated	2026-09-28

Product Overview

Terminal for printed circuit board, rated voltage: 400 V, pitch: 5,08 mm, number of poles: 3, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: gray

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of potentials: 3, number of rows: 1, number of poles per row: 3, family of articles: MKDSN 2.5, pitch: 5.08 mm, type of connection: Screw connection with traction capsule, mounting: Wave soldering, Conductor/PCB connection direction: 0 °, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 2,5/ 3-5,08 GY SZS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.