

## INDUSTRIAL COMPONENT DATA

# MKDSP 25/ 6-15,00 BK 1081869 PHOENIX CONTACT Terminal for printed circuit board, step: 15 mm, number of pole..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSP 25/ 6-15,00 BK



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | MKDSP 25/ 6-15,00 BK           |
| Catalog number  | 1081869                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 100 Pcs                        |
| Document ID     | EO-E751C7193F                  |
| Generated       | 2026-09-29                     |

## Product Overview

Terminal for printed circuit board, step: 15 mm, number of poles: 6, color: black

Terminal block for printed circuit board, nominal current: 125 A, nominal voltage (III/2): 1000 V, nominal section: 35 mm<sup>2</sup>, number of rows: 1, number of poles per row: 6, article family: MKDSP 25, pitch: 15 mm, connection type: Screw connection with traction capsule, screw clamping form: Z2L Pozidriv with longitudinal groove, Mounting: Wave Soldering, Conductor/PCB Connection Direction: 0°, Color: Black, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 4.5mm, Number of Solder Pins per Potential: 4, Packaging Type: Boxed

Printed circuit board terminal, nominal current: 125 A, rated voltage (III/2): 1000 V, nominal cross section: 35 mm<sup>2</sup>, number of rows: 1, number of positions per row: 6, product range: MKDSP 25, pitch: 15 mm, connection method: Screw connection with tension sleeve, screw head form: Z2L Slotted Pozidriv, mounting: Wave soldering, conductor/PCB connection direction: 0°, color: black, Pin layout: Linear pinning, Solder pin [P]: 4.5 mm, number of solder pins per potential: 4, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family MKDSP 25

Product line COMBICON Terminals XL

Number of positions 6

Pitch 15 mm

Number of rows 1  
Pin layout Linear pinning  
Solder pins per potential 4  
Data management status  
Article revision 01  
Electrical propertiesNominal current IN 125 A  
Nominal voltage UN 1000 V  
Rated voltage (III/3) 1000 V  
Rated surge voltage (III/3) 8 kV  
Rated voltage (III/2) 1000 V  
Rated surge voltage (III/2) 8 kV  
Rated voltage (II/2) 1000 V  
Rated surge voltage (II/2) 8 kV  
Connection dataConnection technology  
Type Standard  
Nominal cross section 35 mm<sup>2</sup>  
Conductor connection  
Connection method Screw connection with tension sleeve  
Conductor cross section rigid 0.5 mm<sup>2</sup> ... 35 mm<sup>2</sup>  
Conductor cross section flexible 0.5 mm<sup>2</sup> ... 35 mm<sup>2</sup>  
Conductor cross section AWG 20 ... 2  
Conductor cross section flexible, with ferrule without plastic sleeve 1 mm<sup>2</sup> ... 35 mm<sup>2</sup>  
Conductor cross section, flexible, with ferrule, with plastic sleeve 1.5 mm<sup>2</sup> ... 35 mm<sup>2</sup>  
2 conductors with same cross section, solid 0.5 mm<sup>2</sup> ... 6 mm<sup>2</sup>  
2 conductors with same cross section, flexible 0.5 mm<sup>2</sup> ... 6 mm<sup>2</sup>  
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.5 mm<sup>2</sup> ... 4 mm<sup>2</sup>  
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm<sup>2</sup> ... 16 mm<sup>2</sup>  
Stripping length 18 mm  
Drive form screw head Slotted Pozidriv (Z2L)  
Tightening torque 2.5 Nm ... 4.5 Nm (  
Information on the aluminum conductor  
Cross sec...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSP 25/ 6-15,00 BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.