INDUSTRIAL COMPONENT DATA

MM-TML (EX4,2)R C1 TR/BK 0803979 PHOENIX CONTACT Label

Brand: PHOENIX CONTACT | Manufacturer Part Number: MM-TML (EX4,2)R C1 TR/BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MM-TML (EX4,2)R C1 TR/BK
Catalog number	0803979
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-A378D23333
Generated	2026-11-19

Product Overview

Label
Label, Roll, transparent/black, unlabeled, labelable with: THERMOFOX, THERMOMARK GO, THERMOMARK GO. K, mounting class: glued, usable surface: endless x 3.2 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0803979
Packing unit 1 pc
Catalog page Page 53 (C-3-2017)
GTIN 4055626212548
Weight per Piece (excluding packing) 50.600 g
Custom tariff number 96121010
Country of origin CN (China)
Dimensions
Length (b) 8 m
Width (a) 4.2 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color transparent
Type adhesive
Components free from silicone, halogen, and cadmium
Material Polyester
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0 24190208 eCl@ss 4.1 24190208 eCl@ss 5.0 27149103 eCl@ss 5.1 27141100 eCl@ss 6.0 27149100 eCl@ss 7.0 27149129 eCl@ss 8.0 27149129 eCl@ss....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MM-TML (EX4,2)R C1 TR/BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.