INDUSTRIAL COMPONENT DATA

MM-WMS 3,2 (EX5)R C1 YE/BK 1116139 PHOENIX CONTACT Heat-shrink sleeve, Roll, yellow/black, unlabeled, labela..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MM-WMS 3,2 (EX5)R C1 YE/BK

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	MM-WMS 3,2 (EX5)R C1 YE/BK
Catalog number	1116139
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-94FDC54D16
Generated	2026-11-19

Product Overview

Heat-shrink sleeve, Roll, yellow/black, unlabeled, labelable with: THERMOFOX, THERMOMARK GO, THERMOMARK GO. K, Cable Diameter Range: 1 ... 3.2 mm, mounting class: slip, Number of individual indexes: 1, length. Roll: 1.8 m, Text field height: 3.1 mm, Text field width: 1800 mm
Heat shrink tubing, Roll, yellow/black, unlabeled, labelable with: THERMOMARK GO, THERMOMARK GO. K, THERMOFOX, mounting class: slippage, cable diameter range: 1 ... 3.2 mm, usable surface: endless x 3.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MM-WMS 3,2 (EX5)R C1 YE/BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.