

INDUSTRIAL COMPONENT DATA

IL ETH BK DI8 DO4 2TX-XC-PAC 2701388 PHOENIX CONTACT

Bus coupler

Brand: PHOENIX CONTACT | Manufacturer Part Number: IL ETH BK DI8 DO4 2TX-XC-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IL ETH BK DI8 DO4 2TX-XC-PAC
Catalog number	2701388
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-C5C3838EA0
Generated	2026-09-22

Product Overview

Bus coupler

Inline, Bus coupler, Modbus/TCP(UDP), RJ45 female, Digital inputs: 8, 24 VDC, connection technology: 3 conductors, Digital outputs:4, 24 VDC, 500 mA, connection technology:3 conductors, Extreme Condition variant, transmission speed on the local bus:500 kBit/s / 2 MBit/s, protection index: IP20, including Inline connectors and marking fields

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Technical dataDimensionsDimensional drawing
Width 80 mm
Height 119.8 mm
Depth 71.5 mm
Note on dimensions Specifications with connectors
NotesNote on application
Note on application Only for industrial use
InterfacesModbus/TCP (UDP)
Number of interfaces 2
Connection method RJ45 jack
Note on the connection method Auto negotiation and autocrossing
Transmission speed 10/100 Mbps

Transmission physics Ethernet in RJ45 twisted pair
Inline local bus
Number of interfaces 1
Connection method Inline data jumper
Transmission speed 500 kbps / 2 Mbps (automatic detection, no combined system)
Fieldbus: Local bus gateway
Max. number of local bus devices 61 (The on-board I/Os are two devices)
System propertiesSystem limits
Number of supported devices max. 63 (per station)
Number of local bus devices that can be connected max. 61 (The on-board I/Os are two devices)
Number of devices with parameter channel max. 16
Number of supported branch terminals with remote bus branch 0
Module
ID code (hex) none
Input address area 8 bit
Output address area 4 bit
Register length 16 bit
Input dataDigital:
Input name Digital inputs
Description of the input EN 61131-2 type 1
Number of inputs 8
Connection method Inline connector
Connection technology 3-conductor
Input voltage 24 V DC
Input voltage range "0" signal -30 V DC ... 5 V DC
Input voltage range "1" signal 15 V DC ... 30 V DC
Nominal input voltage UIN 24 V DC
Nominal input current at UIN typ. 3 mA
Typical input current per channel typ. 3 mA
Typical resp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IL ETH BK DI8 DO4 2TX-XC-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.